



VFD Program for Carlsen Receiving Hoppers

THESE SETTINGS ARE FOR VFD'S WITH A "GREEN" COLORED DISPLAY ON THE KEYPAD

ALL SETTINGS ARE AT DEFAULT EXCEPT FOR THE FOLLOWING

ADDRESS	SET TO	ALTERNATE SETTING	DESCRIPTION
001	3		READ & SET TO 116
018	3.0		ACCEL TIME
019	2.0		DECEL TIME
023	1		% READOUT
033	SET TO MOTOR FULL LOAD AMPS (FLA)		MOTOR FLA
036	3 WIRE		S2 SELECTION
055	2 SECOND		POWER LOSS

PLEASE LOOK ON THE MOTOR DESIGNATION PLAQUE TO FIND THE FLA VALUE.

Updated 2/10/05

VFD Program for Carlsen Receiving Hoppers

THESE SETTINGS ARE FOR VFD'S WITH A "RED" COLORED DISPLAY ON THE KEYPAD

ALL SETTINGS ARE AT DEFAULT EXCEPT FOR THE FOLLOWING

ADDRESS	SET TO	ALTERNATE SETTING	DESCRIPTION
001	3		READ & SET TO 116
019	3.0		ACCEL TIME
020	2.0		DECEL TIME
024	1		% READOUT
032	SET TO MOTOR FULL LOAD AMPS (FLA)		MOTOR FLA
035	1 = 3 WIRE		S2 SELECTION
051	2 SECOND RIDE THROUGH		POWER LOSS

PLEASE LOOK ON THE MOTOR DESIGNATION PLAQUE TO FIND THE FLA VALUE.

Updated 2/10/05