



GP5 VFD Program for 2 hp Sump

THESE SETTINGS ARE FOR VFD'S WITH A "GREEN" COLORED DISPLAY ON THE KEYPAD

ALL SETTINGS ARE AT DEFAULT EXCEPT FOR THE FOLLOWING

ADDRESS	SET TO	ALTERNATE SETTING	DESCRIPTION
001	3		READ AND SET TO 116
018	2.0		ACCEL TIME
019	1.0		DECEL TIME
023	1		% READOUT
033	SET TO MOTOR FULL LOAD AMPS		MOTOR FLA
036	3 WIRE FORWARD/REVERSE		S2 SELECTION
041	1		OUTPUT DURING RUN
055	2 SECOND		POWER LOSS

PLEASE LOOK ON THE MOTOR DESIGNATION PLAQUE TO FIND THE FLA VALUE.

Updated 2/10/05

GP5 VFD Program for 2 hp Sump

THESE SETTINGS ARE FOR VFD'S WITH A "RED" COLORED DISPLAY ON THE KEYPAD

ALL SETTINGS ARE AT DEFAULT EXCEPT FOR THE FOLLOWING

ADDRESS	SET TO	ALTERNATE SETTING	DESCRIPTION
001	3		READ AND SET TO 116
019	2.0		ACCEL TIME
020	1.0	220/320 = 2.0	DECEL TIME
024	1		% READOUT
032	SET TO FULL LOAD AMPS		MOTOR FLA
035	3 WIRE FORWARD/REVERSE		S2 SELECTION
040	1		OUTPUT DURING RUN
051	2 SECOND		POWER LOSS

PLEASE LOOK ON THE MOTOR DESIGNATION PLAQUE TO FIND THE FLA VALUE.

Updated 2/10/05